

## Technical Information

# Durlin ANTIRUST

## Product description

**DURLIN ANTIRUST** is an agent that quickly and efficiently removes rust from metal surfaces. It also provides long-term corrosion protection, when the surface is treated with DURLIN Antirust applied base paint for metal.

## Purpose

Apply the product with a brush, shot (degreasing cloth) or by immersion, while for thicker layers of rust it is recommended to sand with a steel brush at the same time. After drying on the surface metal, a syllable powder was formed, which should be removed with a dry cloth or washed with water under pressure. In the case of surfaces that are more affected by the corrosion process, it is necessary to offer.

The technical data are given in order to achieve optimal results by using products manufactured by HELIOS Srbija a.d. Contact our technical service for any additional information. The manufacturer reserves the right to make changes.

## Technical data



### Composition:

Based on orthophosphoric acid

### Density ISO 2811:

~ 1.00 g/cm<sup>3</sup>

### Consumption:

Depending on the rust deposits

### Packaging:

1 l

### Shelf and storage:

Originally closed product, stored in a dry place, protected from direct sunlight (+ 5 °C to + 25 °C) is usable for 60 months.

### Note:

When applying, use protective equipment with mandatory ventilation of the work area. Dispose of bulk material and packaging waste as hazardous waste.